

Safety Data Sheet dated 29/4/2016, version 1 In compliance with Regulation (EC) 2015/830 SECTION 1: Identification of the substance/mixture and of the company/undertaking 1.1. Product identifier Mixture identification: Trade name: FRYFIX TAB Product type: Caustic cleaner 1.2. Relevant identified uses of the substance or mixture and uses advised against Recommended use: Washing and cleaning products (including solvent based products) Uses advised against: Not available 1.3. Details of the supplier of the safety data sheet Supplier: AirChem Consumables, LOB 10, Office # 10F14, JAFZA, Dubai, UAE- Tel: +971-4-881 8084, Fax: +971-4-881 6022, Email: airacc@acc.ae Competent person responsible for the safety data sheet: airacc@acc.ae 1.4. Emergency telephone number AirChem Consumables, Tel: +971-4-881 8084, Fax: +971-4-881 6022, Email: airacc@acc.ae (from Sunday to Thursday from 09 AM to 6 PM; Saturdays 09 AM to 2:30 PM) A list of Poison Control Centers is available at the following link: http://www.who.int/gho/phe/chemical_safety/poisons_centres/en/ **SECTION 2: Hazards identification** 2.1. Classification of the substance or mixture EC regulation criteria 1272/2008 (CLP) \diamond Danger, Skin Corr. 1A, Causes severe skin burns and eye damage. \diamond Danger, Eye Dam. 1, Causes serious eye damage. () Warning, STOT SE 3, May cause respiratory irritation. Aquatic Chronic 3, Harmful to aquatic life with long lasting effects. Adverse physicochemical, human health and environmental effects: 2.2. Label elements EC regulation criteria 1272/2008 (CLP) Hazard pictograms: Danger Hazard statements: H314 Causes severe skin burns and eye damage.

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P260 Do not breathe dust or mist.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/clothing and eye/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor.

Special Provisions:

None

FFRIYFIXTAB/1

Page n. 1 of 11

Contents: Sodium hydroxide disodium metasilicate Troclosene sodium, dihydrate Special provisions according to Annex XVII of REACH and subsequent amendments: None 2.3. Other hazards vPvB Substances: None - PBT Substances: None Other Hazards: No other hazards **SECTION 3: Composition/information on ingredients** 3.1. Substances Not applicable 3.2. Mixtures Hazardous components within the meaning of the CLP regulation and related classification: 20-30 % Sodium hydroxide REACH Nº. 01-2119457892-27-XXXX, Index number: 011-002-00-6, CAS: 1310-73-2, EC: 215-185-5 \diamond 3.2/1A Skin Corr. 1A H314 20-30 % disodium metasilicate REACH N° 01-2119449811-37-XXXX, Index number: 014-010-00-8, CAS: 6834-92-0, EC: 229-912-9 \diamond 2.16/1 Met. Corr. 1 H290 \diamond 3.2/1B Skin Corr. 1B H314 3.8/3 STOT SE 3 H335 20-30 % Sodium carbonate REACH N°: 01-2119485498-19-XXXX, Index number: 011- 005-00-2, CAS: 497-19-8, EC: 207-838-8 \Diamond 3.3/2 Eye Irrit. 2 H319 1-5% Troclosene sodium, dihydrate Index number: 613-030-01-7, CAS: 51580-86-0, EC: 220-767-7 3.1/4/Oral Acute Tox. 4 H302 3.3/2 Eye Irrit. 2 H319 $\langle \rangle$ 3.8/3 STOT SE 3 H335 \diamond 4.1/A1 Aquatic Acute 1 H400 \diamond 4.1/C1 Aquatic Chronic 1 H410 EUH031

Declaration of ingredients according to Detergent Regulation 648/2004: phosphates 15 - 30 %

For the complete text of the hazard and risk phrases refer to paragraph 16

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

OBTAIN IMMEDIATE MEDICAL ATTENTION.

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately. Protect uninjured eye.

In case of Ingestion:

FFRIYFIXTAB/1

Page n. 2 of 11

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

In case of inhalation, consult a doctor immediately and show him packing or label.

4.2. Most important symptoms and effects, both acute and delayed

None

- 4.3. Indication of any immediate medical attention and special treatment needed
 - In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Treatment:

None

SECTION 5: Firefighting measures

- 5.1. Extinguishing media
 - Suitable extinguishing media: Water.

Carbon dioxide (CO2). Extinguishing media which must not be used for safety reasons: None in particular.

- 5.2. Special hazards arising from the substance or mixture Do not inhale explosion and combustion gases. Burning produces heavy smoke.
- 5.3. Advice for firefighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

- 6.1. Personal precautions, protective equipment and emergency procedures
 - Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains. Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

- Suitable material for taking up: absorbing material, organic, sand
- 6.3. Methods and material for containment and cleaning up
 - Wash with plenty of water.
- 6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.
Use localized ventilation system.
Don't use empty container before they have been cleaned.
Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
Contamined clothing should be changed before entering eating areas.
Do not eat or drink while working.
See also section 8 for recommended protective equipment.
7.2. Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed. Incompatible materials:

FFRIYFIXTAB/1

Page n. 3 of 11

None in particular. Instructions as regards storage premises: Adequately ventilated premises. 7.3. Specific end use(s) For more information see Technical date bulletin None in particular **SECTION 8: Exposure controls/personal protection** 8.1. Control parameters Contained substances Sodium hydroxide - CAS: 1310-73-2 ACGIH - STE mg/m3(15min): C 2 - STE ppm: C 1.22 - Behaviour: Binding -Notes: Ingestion: burns to mouth and esophagus, perforation of the gastrointestinal tract. Necrotic tissue. - Critical effects: C irritation of the upper respiratory tract, eye and skin disodium metasilicate - CAS: 6834-92-0 ACGIH - LTE mg/m3(8h): 10 - Behaviour: Binding - Notes: respirable fraction. ACGIH - LTE mg/m3(8h): 3 - Behaviour: Binding - Notes: alveolar fraction Troclosene sodium, dihydrate - CAS: 51580-86-0 ACGIH - LTE mg/m3(8h): 10 **DNEL Exposure Limit Values** Sodium hydroxide - CAS: 1310-73-2 Worker Professional: 1 mg/m3 - Consumer: 1 - U.M.: mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, local effects disodium metasilicate - CAS: 6834-92-0 Consumer: 0.74 - U.M.: mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects Worker Professional: 6.22 mg/m3 - Consumer: 1.55 - U.M.: mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects Worker Professional: 1.49 mg/kg - Consumer: 0.74 - U.M.: mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects Sodium carbonate - CAS: 497-19-8 Worker Professional: 10 mg/m3 - Consumer: 10 - U.M.: mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, local effects **PNEC Exposure Limit Values** disodium metasilicate - CAS: 6834-92-0 Target: Marine water - Value: 1 mg/l Target: Fresh Water - Value: 7.5 mg/l Target: Occasional issue - Value: 1000 mg/l Target: Sewerage treatment plants - Value: 7.5 mg/l 8.2. Exposure controls Eye protection: Use close fitting safety goggles, don't use eye lens. Protection for skin: Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton. Protection for hands: Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber. Respiratory protection: Use respiratory protection where ventilation is insufficient or exposure is prolonged. Use adequate protective respiratory equipment. Thermal Hazards: None Environmental exposure controls: None Appropriate engineering controls: None

FFRIYFIXTAB/1 Page n. 4 of 11

SECTION 9: Physical and chemical properties 9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes:
Appearance and colour:	white powder pressed into tabs		
Odour:	Negligible		
Odour threshold:	n.av. mg/m3		
pH:	na		
Melting point / freezing point:	na °C		
Initial boiling point and boiling range:	na °C		
Flash point:	na ℃		
Evaporation rate:	na		
Solid/gas flammability:	Not flammable		
Upper/lower flammability or explosive limits:	na % v/v		
Vapour pressure:	n.av. kPa		
Vapour density (air=1):	> 1		
Relative density:	0.9 g/ml		
Solubility in water:	Complete under normal use conditions.		
Solubility in oil:	na		
Partition coefficient (n- octanol/water):	na		
Auto-ignition temperature:	na ℃		
Decomposition temperature:	na C		
Viscosity:	n.av. mPa.s		
Explosive properties:	Not explosive		
Oxidizing properties:	Not Oxidant		

9.2. Other information

FFRIYFIXTAB/1 Page n. 5 of 11

Properties	Value	Method:	Notes:
Miscibility:	Complete in water		
Fat Solubility:	na		
Conductivity:	na		
Substance Groups relevant properties:	n.av.		

SECTION 10: Stability and reactivity

- 10.1. Reactivity
 - Stable under normal conditions
- 10.2. Chemical stability
 - Stable under normal conditions
- 10.3. Possibility of hazardous reactions

It may generate flammable gases on contact with halogenated organic substances, and elementary metals.

- 10.4. Conditions to avoid Stable under normal conditions.
- 10.5. Incompatible materials
 - None in particular.
- 10.6. Hazardous decomposition products None.

SECTION 11: Toxicological information

11.1. Information on toxicological effects Toxicological information of the mixture: Not applicable

Toxicological information of the main substances found in the mixture:

Sodium hydroxide - CAS: 1310-73-2

Type: a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat - Op.: = - Value: 2000 - U.M.: mg/kg Test: LC50 - Route: Inhalation - Species: Mouse - Op.: = - Value: 4800 - U.M.: mg/l -Duration: 1 hour

Test: LD50 - Route: Skin - Species: Rabbit - Op.: = - Value: 1350 - U.M.: mg/kg

Test: LCLo - Route: Oral - Species: Rabbit - Op.: = - Value: 500 - U.M.: mg/kg Type: b) skin corrosion/irritation:

Test: Skin Corrosive - Route: Skin - Op.: Positive - Source: OECD 435 - Notes: In vitro study

Test: Eye Corrosive - Route: Skin - Species: Rabbit - Op.: Positive - Notes: irreversible effects

disodium metasilicate - CAS: 6834-92-0

Type: a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat - Op.: > - Value: 1153 - U.M.: mg/kg

Test: LD50 - Route: Oral - Species: Rat - Op.: < - Value: 1349 - U.M.: mg/kg

Test: LC50 - Route: Inhalation - Species: Rat - Op.: > - Value: 2.06 - U.M.: mg/l

Test: LD50 - Route: Skin - Species: Rat - Op.: > - Value: 5000 - U.M.: mg/kg - Duration: 4 hours

Test: NOAEL - Route: Oral - Species: Rat - Op.: = - Value: 227 - U.M.: mg/kg

Test: NOAEL - Route: Oral - Species: Mouse - Op.: = - Value: 260 - U.M.: mg/kg Type: b) skin corrosion/irritation:

Test: Skin Corrosive - Route: Skin - Species: Rat - Op.: Positive Type: c) serious eye damage/irritation:

Test: Eye Corrosive - Route: EYES - Species: Rabbit - Op.: Positive

FFRIYFIXTAB/1

Page n. 6 of 11

Sodium carbonate - CAS: 497-19-8
Type: a) acute toxicity:
Test: LD50 - Route: Oral - Species: Rat - Op.: = - Value: 2800 - U.M.: mg/kg
Test: LD50 - Route: Oral - Species: Rat - Op.: = - Value: 4090 - U.M.: mg/kg
Test: LC50 - Route: Inhalation - Species: Mouse - Op.: = - Value: 1.2 - U.M.: mg/l - Duration: 2 hours
Test: LC50 - Route: Inhalation - Species: Rat - Op.: = - Value: 2.3 - U.M.: mg/l - Duration: 2 hours
Test: LD50 - Route: Skin - Species: Rabbit - Op.: > - Value: 2000 - U.M.: mg/kg
Test: LD50 - Route: Skin - Species: Mouse - Op.: = - Value: 117 - U.M.: mg/kg
Test: LC50 - Route: Inhalation - Species: Guinea-pig - Op.: = - Value: 9.8 - U.M.: mg/l - Duration: 2 hours
Troclosene sodium, dihydrate - CAS: 51580-86-0
Type: a) acute toxicity:
Test: LD50 - Route: Oral - Species: Rat - Op.: = - Value: 700 - U.M.: mg/kg

Test: LD50 - Route: Skin - Species: Rabbit - Op.: = - Value: 6000 - U.M.: mg/kg

If not differently specified, the information required in Regulation (EU)2015/830 listed below must be considered as N.A.:

a) acute toxicity;

b) skin corrosion/irritation;

c) serious eye damage/irritation;

d) respiratory or skin sensitisation;

e) germ cell mutagenicity;

f) carcinogenicity;

g) reproductive toxicity;

h) STOT-single exposure;

i) STOT-repeated exposure;

j) aspiration hazard.

SECTION 12: Ecological information

12.1. Toxicity

Based on the information available it is not expected that this product may cause any adverse environmental effect when use instructions and disposal recommendations are followed. Adopt good working practices, so that the product is not released into the environment. List of substances hazardous to the environment and eco-toxicological information available: Sodium hydroxide - CAS: 1310-73-2

Type: a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish - Op.: > - Value: 35 - U.M.: mg/l - Duration h: 96 Endpoint: LC50 - Species: Fish - Op.: < - Value: 189 - U.M.: mg/l - Duration h: 96 Endpoint: LC50 - Species: Fish - Op.: = - Value: 125 - U.M.: mg/l - Duration h: 96 -Notes: Gambusia affinis Endpoint: EC50 - Species: Daphnia - Op.: > - Value: 30 - U.M.: mg/l - Duration h: 48 Endpoint: EC50 - Species: Daphnia - Op.: < - Value: 1000 - U.M.: mg/l - Duration h: 48 Endpoint: EC50 - Species: Daphnia - Op.: = - Value: 40.4 - U.M.: mg/l - Duration h: 48 - Notes: Ceriodaphnia dubia Type: b) Aquatic chronic toxicity: Endpoint: NOEC - Species: Fish - Op.: = - Value: 56 - U.M.: mg/l - Duration h: 96 -Notes: Poecilia reticulata disodium metasilicate - CAS: 6834-92-0 Type: a) Aquatic acute toxicity: Endpoint: LC50 - Species: Fish - Op .: = - Value: 210 - U.M.: mg/l - Duration h: 96 -Notes: Brachydanio rerio Endpoint: LC50 - Species: Fish - Op .: = - Value: 2320 - U.M .: mg/l - Duration h: 96 -Notes: Gambusia affinis Endpoint: EC50 - Species: Daphnia - Op.: = - Value: 1700 - U.M.: mg/l - Duration h:

48 - Notes: Daphnia magna Endpoint: EC50 - Species: Algae - Op.: = - Value: 207 - U.M.: mg/l - Duration h: 72 - Notes: Scenedesmus subspicatus Sodium carbonate - CAS: 497-19-8 Type: a) Aquatic acute toxicity: Endpoint: LC50 - Species: Fish - Op.: = - Value: 300 - U.M.: mg/l - Duration h: 96 -Notes: Lepomis macrochirus Endpoint: EC50 - Species: Daphnia - Op.: = - Value: 200 - U.M.: mg/l - Duration h: 48 - Notes: Ceriodaphnia dubia Endpoint: LC50 - Species: Fish - Op .: = - Value: 740 - U.M.: mg/l - Duration h: 96 -Notes: Gambusia affinis Troclosene sodium, dihvdrate - CAS: 51580-86-0 Type: a) Aquatic acute toxicity: Endpoint: LC50 - Species: Fish - Op .: = - Value: 0.37 - U.M.: mg/l - Duration h: 96 -Notes: Oncorhynchus mykiss Endpoint: LC50 - Species: Fish - Op .: = - Value: 0.43 - U.M.: mg/l - Duration h: 96 -Notes: Perca fluviatilis Endpoint: LC50 - Species: Fish - Op.: = - Value: 0.355 - U.M.: mg/l - Duration h: 96 Endpoint: EC50 - Species: Algae - Op.: = - Value: 0.28 - U.M.: mg/l - Duration h: 48 - Notes: Crustaceans 12.2. Persistence and degradability disodium metasilicate - CAS: 6834-92-0 Biodegradability: Readily biodegradable - Test: Not applicable - Duration: Not applicable -%: Not applicable - Notes: Not applicable Regulation (EC) No. 648/2004 on Detergents and amendments: Surfactant(s) contained in this preparation comply with biodegradability criteria as defined in (EC) regulations on detergents. 12.3. Bioaccumulative potential Sodium hydroxide - CAS: 1310-73-2 Bioaccumulation: Not bioaccumulative - Test: Not applicable Not applicable - Duration: Not applicable - Notes: Not applicable disodium metasilicate - CAS: 6834-92-0 Bioaccumulation: Not bioaccumulative - Test: Not applicable Not applicable - Duration: Not applicable - Notes: Not applicable 12.4. Mobility in soil Sodium hydroxide - CAS: 1310-73-2 Mobility in soil: Mobile - Test: Not applicable Not applicable - Duration: Not applicable -Notes: Not applicable 12.5. Results of PBT and vPvB assessment vPvB Substances: None - PBT Substances: None 12.6. Other adverse effects None **SECTION 13: Disposal considerations** 13.1. Waste treatment methods Product and its residue: Do not dispose in the canals of wastewater, waterways and soil. The codes indicating the type of waste are considered based on the recommendations

and scheduled use of this product. Different codes may be assigned bused on the end user's use and the characteristics of the disposal.

Waste code CER/EWC (2000/532/CE), attributable to the product as:

06 02 04 * Sodium and potassium hydroxide

HP8 - HP5 - HP14

Any remaining product should be disposed of with the material.

Containers/contaminated packaging

Containers, even completely empty, must not be disposed in the environment. The packing which can not be cleaned should be disposed of as the material.

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions.

FFRIYFIXTAB/1

Page n. 8 of 11

In so doing, comply with the local and national regulations currently in force.

SECTION 14: Transport information



14.1 UN number:			
ADR-UN Number:	3262		
IATA-UN Number:	3262		
IMDG-UN Number:	3262		
14.2. UN proper shipping name			
ADR-Shipping Name:	CORROSIVE SOLID, BASIC, INORGANIC, N.O.S. (Sodium		
	hydroxide, Disodium metasilicate)		
IATA-Shipping Name:	CORROSIVE SOLID, BASIC, INÓRGANIC, N.O.S. (Sodium		
11 0	hydroxide, Disodium metasilicate)		
IMDG-Shipping Name:	CORROSIVE SOLID, BASIC, INORGANIC, N.O.S. (Sodium		
11 0	hydroxide, Disodium metasilicate)		
14.3. Transport hazard class(es)			
ADR-Class:	8		
IATA-Class:	8		
IMDG-Class:	8		
14.4. Packing group			
ADR-Packing Group:	II		
IATA-Packing group:	II		
IMDG-Packing group:	II		
14.5. Environmental hazards			
ADR-Enviromental Pollutant:	No		
IMDG-Marine pollutant:	No		
14.6. Special precautions for user			
ADR-Subsidiary risks:	-		
ADR-S.P.:	274		
ADR-Transport category (Tunnel restriction code): 2 (E)			
IATA-Passenger Aircraft:	859		
IATA-Subsidiary risks:	-		
IATA-Cargo Aircraft:	863		
IATA-S.P.:	A3 A803		
IATA-ERG:	8L		
IMDG-EmS:	F-A , S-B		
IMDG-Subsidiary risks:	-		
IMDG-Stowage and handling:	Category B		
IMDG-Segregation: "Separated from" acids.			
14.7. Transport in bulk according to Annex II of Marpol and the IBC Code			
No			

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Dir. 98/24/EC (Risks related to chemical agents at work)
Dir. 2000/39/EC (Occupational exposure limit values)
Regulation (EC) n. 1907/2006 (REACH)
Regulation (EC) n. 1272/2008 (CLP)
Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
Regulation (EU) 2015/830
Regulation (EU) n. 286/2011 (ATP 2 CLP)
Regulation (EU) n. 618/2012 (ATP 3 CLP)
Regulation (EU) n. 487/2013 (ATP 4 CLP)
Regulation (EU) n. 944/2013 (ATP 5 CLP)

FFRIYFIXTAB/1

Page n. 9 of 11

Regulation (EU) n. 605/2014 (ATP 6 CLP) Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications: Restrictions related to the product: No restriction. Restrictions related to the substances contained: No restriction. Volatile Organic compounds - VOCs = 0.00 % Volatile Organic compounds - VOCs = 0.00 g/I Volatile CMR substances = 0.00 % Halogenated VOCs which are assigned the risk phrase R40 = 0.00 % Organic Carbon - C = 0.00 Where applicable, refer to the following regulatory provisions : Regulation (EC) n°648/2004 (detergents).

15.2. Chemical safety assessment Not available

SECTION 16: Other information

Full text of phrases referred to in Section 3: H314 Causes severe skin burns and eye damage.
H290 May be corrosive to metals.
H335 May cause respiratory irritation.
H319 Causes serious eye irritation.
H302 Harmful if swallowed.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
EUH031 Contact with acids liberates toxic gas.

Hazard class and hazard category	Code	Description
Met. Corr. 1	2.16/1	Substance or mixture corrosive to metals, Category 1
Acute Tox. 4	3.1/4/Oral	Acute toxicity (oral), Category 4
Skin Corr. 1A	3.2/1A	Skin corrosion, Category 1A
Skin Corr. 1B	3.2/1B	Skin corrosion, Category 1B
Eye Dam. 1	3.3/1	Serious eye damage, Category 1
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3
Aquatic Acute 1	4.1/A1	Acute aquatic hazard, category 1
Aquatic Chronic 1	4.1/C1	Chronic (long term) aquatic hazard, category 1
Aquatic Chronic 3	4.1/C3	Chronic (long term) aquatic hazard, category 3

This safety data sheet has been completely updated in compliance to Regulation 2015/830. This document was prepared by a competent person who has received appropriate training. This MSDS cancels and replaces any preceding release.

FFRIYFIXTAB/1 Page n. 10 of 11

Where applicable, refer to the following regulatory provisions :

Council Directive 67/548/EEC (Classification, packaging and labelling of dangerous substances) and subsequent amendments; Regulation (EC) n⁹272/2 008; Regulation (EC) N. 790/2009 (annex VI), Regulation (EC) n. 1907/2006 (REACH).

Commission Directive 1999/45/EC (Classification, packaging and labelling of dangerous preparation) and subsequent amendments; Commission Directive n. 2006/8/CE. Directive 2012/18/EU (Seveso III)

Directive 2013/10/EU (aerosols) amending Directive 75/324/EEC on the approximation of the laws of the Member States relating to aerosol dispensers in order to adapt its labelling provisions to Regulation (EC) n°1272/2008 on class ification, labelling and packaging of substances and mixtures and subsequent amendments.

Regulation (EC) No 1223/2009 on cosmetic products and subsequent amendments. Regulation (EU) No 126/2013 amending Annex XVII to Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) and subsequent amendments. Regulation (EC) N. 304/2003 and subsequent amendments. Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products and subsequent amendments.

Directives 91/156/CEE, 91/689/CEE, 94/62/CE (Disposal of waste) and subsequent amendments.

The European Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), current edition.

Regulations IATA/ICAO = Dangerous Goods Regulations by air, current edition.

RID = Regulations concerning the International Carriage of Dangerous Goods by Rail, current edition.

IMDG Code = International Maritime Dangerous Goods Code produced by the International Maritime Organization (IMO), current edition.

Main bibliographic sources:

ESIS: European chemical Substances Information System and Environmental hazard classification.

Occupational exposure limit values (Commission Directives 2000/39/EC and 2006/15/CE) NIOSH - Registry of toxic effects of chemical substances (1983)

Material Safety Data Sheets of chemicals, REACH database

Material Safety Data Sheet and Technical Data of raw material as by Supplier.

Abbreviations and acronyms:

TLV-TWA = Threshold Limit Value- time-weighed average, 8-hour workday, 40-hour workweek; TLV-STEL-15 min = Threshold Limit Values - Short Term Exposure Limit; TLV-C = Ceiling exposure limit; Notes: IBE= Biological Exposure Indices; SEN= sensitizer; Skin= Can be absorbed through the skin. Carcinogenicity categories: A1 / A2 = confirmed / suspected human carcinogen; A3 = Animal carcinogen; A4 / A5 = Not Classificable/not suspected as a human carcinogen. ACGIH = American Conference on Governmental Industrial Hygienists. OEL =Occupational Exposure Limit. VLPE = Occupational Exposure Limit Values. LTE =long term exposure, STE=short term exposure.

n.av.= Not Available, n.a. = not applicable; LD50=lethal dose (solids and liquids), LC50=lethal concentration (gases) that will kill 50% of the test animals; ADR= European Agreement concerning the International Carriage of Dangerous Goods by Road. Regulations IATA/ICAO = Dangerous Goods Regulations by air, current edition.

RID = Regulations concerning the International Carriage of Dangerous Goods by Rail, current edition. IMDG Code = International Maritime Dangerous Goods Code produced by the International Maritime Organization (IMO), current edition.

PBT = Persistent, Bioaccumulative and Toxic substances.; vPvB = very Persistent and very Bioaccumulative substances; CMR = Carcinogenic, mutagenic or reproduction toxic substances. The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

FFRIYFIXTAB/1 Page n. 11 of 11